

## DECLARATION OF PERFORMANCE NO: 0609/13252/2012

1. Unique identification code of the product-type: structured underlay VAPOZINC  
11010874 / 9800285
2. Intended use: Compensation and drainage of moisture.
3. Manufacturer: RHEINZINK GmbH & Co. KG  
Bahnhofstraße 90  
45711 Datteln  
Germany
4. System of AVCP: 2+
5. Harmonised standard: EN 13252:2016  
Notified body: 0799-CPD  
Kiwa MPA Bautest GmbH  
Gutenbergstraße 29  
D-48268 Greven  
Germany


6. Declared performances:


Essential characteristics	Performance
Tensile strength MD Tmax.	4.6 kN/m - 0.6 kN/m
Tensile strength CMD Tmax.	3.2 kN/m - 0.4 kN/m
Water flow capacity in the plane	1.5 · 0.001m <sup>2</sup> /s – 0.1 · 0.001m <sup>2</sup> /s

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Datteln, 01.02.2023

  
.....  
Bettina Wellner  
Head of Quality Control

  
.....  
Steven Paton  
Head of department  
Product management and application  
technology